



Description

JMT N-channel Enhancement Mode Power MOSFET

Features




- 68V, 80A
- $R_{DS(ON)} < 8.6\text{m}\Omega$ @ $V_{GS} = 10\text{V}$
- Advanced Trench Technology
- Provide Excellent $R_{DS(ON)}$ and Low Gate Charge
- Lead free product is acquired

Application

- Load Switch
- PWM Application
- Power management



100% UIS TESTED!
100% ΔV_{ds} TESTED!



TO-252-4R(DPAK) top view

Marking and pin Assignment

Schematic Diagram

Package Marking and Ordering Information

| Device Marking | Device | OUTLINE | Device Package | TUBE (PCS) | Inner BOX (PCS) | Per Carton (PCS) |
|----------------|------------|---------|----------------|------------|-----------------|------------------|
| JMTK70N07A | JMTK70N07A | TAPING | TO-252-4R | 13inch | 2500 | 25000 |

Absolute Maximum Ratings ($T_c = 25^\circ\text{C}$ unless otherwise specified)

| Symbol | Parameter | | Max. | Units |
|-----------------|---|---------------------------|-------------|---------------------------|
| V_{DSS} | Drain-Source Voltage | | 68 | V |
| V_{GSS} | Gate-Source Voltage | | ± 20 | V |
| I_D | Continuous Drain Current | $T_c = 25^\circ\text{C}$ | 80 | A |
| | | $T_c = 100^\circ\text{C}$ | 52 | A |
| I_{DM} | Pulsed Drain Current ^{note1} | | 320 | A |
| E_{AS} | Single Pulsed Avalanche Energy ^{note2} | | 121 | mJ |
| P_D | Power Dissipation | $T_c = 25^\circ\text{C}$ | 116 | W |
| $R_{\theta JC}$ | Thermal Resistance, Junction to Case | | 0.85 | $^\circ\text{C}/\text{W}$ |
| T_J, T_{STG} | Operating and Storage Temperature Range | | -55 to +175 | $^\circ\text{C}$ |

**Electrical Characteristics** ($T_J=25^\circ\text{C}$ unless otherwise specified)

| Symbol | Parameter | Test Condition | Min. | Typ. | Max. | Units |
|---|--|--|------|------|-----------|------------------|
| Off Characteristics | | | | | | |
| $V_{(\text{BR})\text{DSS}}$ | Drain-Source Breakdown Voltage | $V_{GS}=0\text{V}$, $I_D=250\mu\text{A}$ | 68 | - | - | V |
| I_{DSS} | Zero Gate Voltage Drain Current | $V_{DS}=68\text{V}$, $V_{GS}=0\text{V}$, | - | - | 1.0 | μA |
| I_{GSS} | Gate to Body Leakage Current | $V_{DS}=0\text{V}$, $V_{GS}=\pm 20\text{V}$ | - | - | ± 100 | nA |
| On Characteristics | | | | | | |
| $V_{GS(\text{th})}$ | Gate Threshold Voltage | $V_{DS}=V_{GS}$, $I_D=250\mu\text{A}$ | 2 | - | 4 | V |
| $R_{DS(\text{on})}$ | Static Drain-Source on-Resistance note3 | $V_{GS}=10\text{V}$, $I_D=30\text{A}$ | - | 6.6 | 8.6 | $\text{m}\Omega$ |
| Dynamic Characteristics | | | | | | |
| C_{iss} | Input Capacitance | $V_{DS}=25\text{V}$, $V_{GS}=0\text{V}$, $f=1.0\text{MHz}$ | - | 4062 | - | pF |
| C_{oss} | Output Capacitance | | - | 261 | - | pF |
| C_{rss} | Reverse Transfer Capacitance | | - | 231 | - | pF |
| Q_g | Total Gate Charge | $V_{DS}=30\text{V}$, $I_D=20\text{A}$, $V_{GS}=10\text{V}$ | - | 35 | - | nC |
| Q_{gs} | Gate-Source Charge | | - | 11 | - | nC |
| Q_{gd} | Gate-Drain("Miller") Charge | | - | 9 | - | nC |
| Switching Characteristics | | | | | | |
| $t_{d(on)}$ | Turn-on Delay Time | $V_{DS}=30\text{V}$, $I_D=20\text{A}$, $R_{\text{GEN}}=6\Omega$, $V_{GS}=10\text{V}$ | - | 15 | - | ns |
| t_r | Turn-on Rise Time | | - | 94 | - | ns |
| $t_{d(off)}$ | Turn-off Delay Time | | - | 46 | - | ns |
| t_f | Turn-off Fall Time | | - | 32 | - | ns |
| Drain-Source Diode Characteristics and Maximum Ratings | | | | | | |
| I_s | Maximum Continuous Drain to Source Diode Forward Current | - | - | 80 | - | A |
| I_{sM} | Maximum Pulsed Drain to Source Diode Forward Current | - | - | 320 | - | A |
| V_{SD} | Drain to Source Diode Forward Voltage | $V_{GS}=0\text{V}$, $I_s=80\text{A}$ | - | - | 1.2 | V |
| trr | Body Diode Reverse Recovery Time | $T_J=25^\circ\text{C}$ $I_F=20\text{A}$, $dI/dt=100\text{A}/\mu\text{s}$ | - | 78 | - | ns |
| Qrr | Body Diode Reverse Recovery Charge | | - | 51 | - | nC |

Notes:1. Repetitive Rating: Pulse Width Limited by Maximum Junction Temperature

2. EAS condition: $T_J=25^\circ\text{C}$, $V_{DD}=35\text{V}$, $V_G=10\text{V}$, $R_G=25\Omega$, $L=0.5\text{mH}$, $I_{AS}=22\text{A}$ 3. Pulse Test: Pulse Width $\leq 300\mu\text{s}$, Duty Cycle $\leq 0.5\%$

Typical Performance Characteristics

Figure 1: Output Characteristics




Figure 3: On-resistance vs. Drain Current




Figure 5: Gate Charge Characteristics




Figure 2: Typical Transfer Characteristics




Figure 4: Body Diode Characteristics




Figure 6: Capacitance Characteristics




Figure 7: Normalized Breakdown Voltage vs. Junction Temperature




Figure 9: Maximum Safe Operating Area




Figure.11: Maximum Effective Transient Thermal Impedance, Junction-to-Case




Figure 8: Normalized on Resistance vs. Junction Temperature





Figure 10: Maximum Continuous Drain Current vs. Case Temperature



Test Circuit




Figure1:Gate Charge Test Circuit & Waveform



Figure 2: Resistive Switching Test Circuit & Waveforms





Figure 3:Unclamped Inductive Switching Test Circuit & Waveforms


Package Mechanical Data-TO-252-4R



TO-252

| Ref. | Dimensions | | | | | |
|------|-------------|------|-------|----------|------|-------|
| | Millimeters | | | Inches | | |
| | Min. | Typ. | Max. | Min. | Typ. | Max. |
| A | 2.10 | | 2.50 | 0.083 | | 0.098 |
| A2 | 0 | | 0.10 | 0 | | 0.004 |
| B | 0.66 | | 0.86 | 0.026 | | 0.034 |
| B2 | 5.18 | | 5.48 | 0.202 | | 0.216 |
| C | 0.40 | | 0.60 | 0.016 | | 0.024 |
| C2 | 0.44 | | 0.58 | 0.017 | | 0.023 |
| D | 5.90 | | 6.30 | 0.232 | | 0.248 |
| D1 | 5.30REF | | | 0.209REF | | |
| E | 6.40 | | 6.80 | 0.252 | | 0.268 |
| E1 | 4.63 | | | 0.182 | | |
| G | 4.47 | | 4.67 | 0.176 | | 0.184 |
| H | 9.50 | | 10.70 | 0.374 | | 0.421 |
| L | 1.09 | | 1.21 | 0.043 | | 0.048 |
| L2 | 1.35 | | 1.65 | 0.053 | | 0.065 |
| V1 | | 7° | | | 7° | |
| V2 | 0° | | 6° | 0° | | 6° |

Reel Specification-TO-252-4R



| Ref. | Dimensions | | | | | |
|------|-------------|-------|-------|--------|-------|-------|
| | Millimeters | | | Inches | | |
| | Min. | Typ. | Max. | Min. | Typ. | Max. |
| W | 15.90 | 16.00 | 16.10 | 0.626 | 0.630 | 0.634 |
| E | 1.65 | 1.75 | 1.85 | 0.065 | 0.069 | 0.073 |
| F | 7.40 | 7.50 | 7.60 | 0.291 | 0.295 | 0.299 |
| D0 | 1.40 | 1.50 | 1.60 | 0.055 | 0.059 | 0.063 |
| D1 | 1.40 | 1.50 | 1.60 | 0.055 | 0.059 | 0.063 |
| P0 | 3.90 | 4.00 | 4.10 | 0.154 | 0.157 | 0.161 |
| P1 | 7.90 | 8.00 | 8.10 | 0.311 | 0.315 | 0.319 |
| P2 | 1.90 | 2.00 | 2.10 | 0.075 | 0.079 | 0.083 |
| A0 | 6.85 | 6.90 | 7.00 | 0.270 | 0.271 | 0.276 |
| B0 | 10.45 | 10.50 | 10.60 | 0.411 | 0.413 | 0.417 |
| K0 | 2.68 | 2.78 | 2.88 | 0.105 | 0.109 | 0.113 |
| T | 0.24 | | 0.27 | 0.009 | | 0.011 |
| t1 | 0.10 | | | 0.004 | | |
| 10P0 | 39.80 | 40.00 | 40.20 | 1.567 | 1.575 | 1.583 |



Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co.,Ltd assumes no responsibility for the consequences of use without consideration for such information nor use beyond it.

Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement.

Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information.

is a registered trademark of Jiangsu JieJie Microelectronics Co.,Ltd.
Copyright ©2020 Jiangsu JieJie Microelectronics Co.,Ltd. Printed All rights reserved.